

nano F^{1,1}: Compressed Air & Gas Filtration

GMS 0070

70 scfm Medical Sterile Filter

nano GMS medical sterile filters are specifically designed and manufactured to exceed the requirements for medical gas pipeline systems providing reliable and outstanding air purity that meets internationally certified medical performance levels. Applications include: dental, medical and veterinary.

GENERAL CHARACTERISTICS		
Rated flow (scfm) (1)	70	
OPERATING LIMITS		
Design operating pressure range (psig)	22 to 300	
Design operating temperature range (°F)	35 to 248	
HOUSING CONSTRUCTION		
Materials	pressure die cast aluminum	
Finish	E-Coat™ surface treatment (internal & external) powder paint (external)	
ELEMENT CONSTRUCTION		
Media	borosilicate glass microfiber	
End caps	stainless steel	
Replacement element (part no.)	GE 0105 MS	
COMPONENTS		
Manual drain (part no.)	GFMDK 1500	
Differential pressure indicator / gauge	gauge	
DP (part no.)	GFDP 1500	
AIR CIRCUIT		
Air circuit connections (NPT)	1/2"	

⁽¹⁾ At 100 psig. For all other pressures, contact support@nano-purification.com.

Features

HOUSING FEATURES

- Designed in accordance with ASME pressure vessel standards.
- Carries CRN (Canadian Registration Numbers) for approved use in every province of Canada.
- "Dead Stop" bowl feature provides full closure without over tightening.
- · 10 year housing warranty

- Optimized seal ensures zero leakage and ease of bowl removal during element replacement.
- No tie rod simplifies element change out and reduces access requirements for bowl removal.
- Comprehensive range of filter mounting accessories


ELEMENT FEATURES

- Third party tested and validated in accordance with NFPA 99, HTM 02-01, ISO 7396-1, and AS 2896.
- 100% integrity tested
- Guaranteed for a minimum of 100 sterilizations at 248°F.
- Stainless steel end caps for compatibility with autoclave sterilization.



Dimensions & Weight

DIMENSIONS	AND WEIGHT
A (ins)	5
B (ins)	1.26
C (ins) *	11.22
D (ins)	1.18
E (ins)	15.6
Weight (lbs)	3.7



nano F^{1,1}: Medical Sterile Filters

ELEMENT GRADES	MS	
DOP efficiency ⁽¹⁾	> 99.9999%	
Particle removal (microns) (2)	0.01	
Recommended operating temperature range (°F)	35 to 212	
Design operating temperature range (°F)	35 to 248	
Maximum autoclave temperature (3)	273	
Pressure drop - clean (psid)	1.5	
Pressure drop - recommended replacement (psid)	6.0	
End cap material	stainless steel	
Flow direction through element	outside to inside	
Maximum steam sterilization cycle	100	
Maximum element life	6 months or 1000 hours	

- (1) As specified in HTM 02-01 medical gas pipeline systems.
- (2) Per ISO 8573.1:2010
- (3) Applies to element only.

Accessories

CONNECTING KITS	FITS	PART NUMBER
Connecting kit (2 Filters)	GMS 0070	GFCK-2 0175



WALL MOUNTING KITS	FITS	PART NUMBER
Wall mounting kit	GMS 0070	GFMK 0175



Technical specifications subject to change without notice. Publication Reference: GMS0070-CA-EN-Version-000 ©2024 Air & Gas Solutions LLC





St. Catharines, Ontario, Canada
Phone: +1 905 684 6266
Email: canadasupport@nano-purification.com