


## RNC 0110-F

### 230/1/60 - 110 scfm refrigerated air dryer

nano R2 RNC high inlet temperature refrigerated air dryers are designed for the unique demands of high temperature compressed air applications. They feature a low pressure drop stainless steel heat exchanger, stainless steel moisture separator, environmentally friendly refrigerants, TXV for precise control and a simple yet powerful electronic controller. RNC offers piece of mind that downstream equipment will be protected from damaging moisture contamination.



#### general characteristics

rated capacity (scfm)*	110
absorbed power (kW)	0.94
full load amps (A)	7.50
power supply (V/Ph/Hz)	230/1/60

#### operating limits

design operating pressure range (psig)	0 - 232
maximum refrigerant working pressure (psig)	392
minimum/maximum ambient temperature (°F)	34 - 110
maximum inlet temperature (°F)	158

#### refrigerant gas/circuit

refrigerant type	R407c
refrigerant charge per circuit (lbs)	1.54

#### compressors

compressor type	rotary
compressor quantity	1
independent gas circuit	1

#### fans

fan type	axial
fan quantity	1

#### air circuit

air circuit connections (NPT)	1½"
-------------------------------	-----

#### ISO class

ISO air quality class (water content)	class 6
---------------------------------------	---------

\*rated flow capacity: at 125 psig & 140°F inlet conditions, 95°F ambient, and a 50°F outlet pressure dew point. For all other conditions, please contact support@n-psi for sizing

#### features

- nano F1 1 micron pre filter included as standard
- stainless steel heat exchanger for maximum durability and corrosion resistance
- CAREL advanced electronic controller
- oversized condenser for high ambient temperatures
- robust refrigeration circuit with fan pressure, high refrigerant pressure and low suction pressure switches
- environmentally friendly R134a and R407C refrigerant
- supplied with 6' power cord for plug and play operation
- timed solenoid drain for reliable condensate removal
- refrigerant gauge for simple diagnostics
- powder coated aluminum panels
- TXV ensures stable dew point performance under varying loads
- stainless steel inlet and outlet connections
- c-UL listed components
- built in reliability with a 1 year warranty with pre-filtration and non-corrosive piping installed

#### advanced microprocessor features

- 3 button digital interface
- dew point display for visual monitoring
- user programmable operating parameters
- status indication for drain, fan and compressor
- drain test and adjustment



Experience. Customer. Service.

**nano-purification solutions llc**  
charlotte, north carolina  
united states

**nano-purification solutions**  
st. catharines, ontario  
canada

**nano-purification solutions ltd**  
gateshead, tyne and wear  
united kingdom

**nano-purification solutions GmbH**  
krefeld, germany

tel: 704.897.2182  
fax: 704.897.2183  
email: support@n-psi.com  
web: www.n-psi.com

[www.n-psi.com](http://www.n-psi.com)

## technical specification

### dimensions & weight

length (ins)	15.9
depth (ins)	34.4
height (ins)	30.0
weight (lbs)	196

