

## RTC 0075-F

115/1/60 - 75 scfm refrigerated air dryer

The nano R<sup>2</sup> range of refrigerated thermal mass cycling dryers are specifically designed for the unique demands of high temperature compressed air applications. These are the optimum choice for fluctuating air flows and harsh environments.



### general characteristics

rated capacity (scfm)*	75
absorbed power (kW)	0.969
full load amps (A)	11.30
power supply (V/Ph/Hz)	115/1/60

### operating limits

design operating pressure range (psig)	0 - 232
maximum refrigerant working pressure (psig)	247
minimum/maximum ambient temperature (°F)	34 - 122
maximum inlet temperature (°F)	158

### refrigerant gas/circuit

refrigerant type	R134a
refrigerant charge per circuit (lbs)	1.08

### compressors

compressor type	piston
compressor quantity	1
independent gas circuit	1

### fans

fan type	axial
fan quantity	1

### air circuit

air circuit connections (NPT)	1½"
-------------------------------	-----

### ISO class

ISO air quality class (water content)	class 6
---------------------------------------	---------

\*rated flow capacity: at 125 psig & 140°F inlet conditions, 95°F ambient, and a 50°F outlet pressure dew point. For all other conditions, please contact support@n-psi for sizing

### features

- nano F1 1 micron pre filter included as standard
- patented dual transfer thermal heat exchanger
- advanced electronic controller
- built in reliability with a 1 year warranty
- 232 psig standard rating for the complete range
- simple refrigeration circuit with no hot gas bypass valve
- wide air paths – trouble free anti-clogging heat exchanger
- self-adjusting and controlling
- environmentally friendly refrigerant and non-toxic “dry” silica mass
- quick easy startup with no pre-start up cooling programming or calibration
- designed for tough Industrial settings

### advanced microprocessor features

- 3 button digital interface
- digital LED display
- outlet air dew point indication
- user programmable operating parameters
- condensate drain control and test function



**nano-purification solutions llc**  
charlotte, north carolina  
united states

**nano-purification solutions**  
st. catharines, ontario  
canada

**nano-purification solutions ltd**  
gateshead, tyne and wear  
united kingdom

**nano-purification solutions GmbH**  
krefeld, germany

tel: 704.897.2182  
fax: 704.897.2183  
email: support@n-psi.com  
web: www.n-psi.com

## technical specification

### dimensions & weight

length (ins)	29.1
depth (ins)	24.3
height (ins)	36.5
weight (lbs)	291

