


## NDX 0175

### 115/1/60 - 175 scfm refrigerated air dryer

nano R4 refrigerated air dryers are designed for reliability, performance and low cost of ownership. They feature a low pressure drop stainless steel heat exchanger, stainless steel moisture separator, environmentally friendly refrigerants, TXV for precise control and a simple yet powerful electronic controller. The R4 offers piece of mind that downstream equipment will be protected from damaging moisture contamination.



#### general characteristics

rated capacity (scfm)*	175
absorbed power (kW)	0.96
full load amps (A)	11.57
power supply (V/Ph/Hz)	115/1/60

#### operating limits

design operating pressure range (psig)	0 - 232
maximum refrigerant working pressure (psig)	247
minimum/maximum ambient temperature (°F)	34 - 122
maximum inlet temperature (°F)	158

#### refrigerant gas/circuit

refrigerant type	R134a
refrigerant charge per circuit (lbs)	1.10

#### compressors

compressor type	rotary
compressor quantity	1
independent gas circuit	1

#### fans

fan type	axial
fan quantity	1

#### air circuit

air circuit connections (NPT)	1½"
-------------------------------	-----

#### ISO class

ISO air quality class (water content)	class 4
---------------------------------------	---------

*\*rated flow capacity: conditions for rating dryers are in accordance with ISO7183 (Option A2). Compressed air at dryer inlet: 100 psig (7 bar) and 100°F (38°C); ambient air temperature: 100°F (38°C); operating on 60Hz power supply. For all other conditions, contact support@n-psi.com*

#### features

- stainless steel heat exchanger for maximum durability and corrosion resistance
- CAREL advanced electronic controller
- oversized condenser for high ambient temperatures
- robust refrigeration circuit with fan pressure, high refrigerant pressure and low suction pressure switches
- environmentally friendly R134a and R407C refrigerant
- supplied with 6' power cord for plug and play operation
- timed solenoid drain for reliable condensate removal
- refrigerant gauge for simple diagnostics
- powder coated aluminum panels
- TXV ensures stable dew point performance under varying loads
- stainless steel inlet and outlet connections
- c-UL listed components
- built in reliability with a 2 year warranty with pre-filtration and non-corrosive piping installed

#### advanced microprocessor features

- 3 button digital interface
- dew point display for visual monitoring
- user programmable operating parameters
- status indication for drain, fan and compressor
- drain test and adjustment



## technical specification

### dimensions & weight

length (ins)	15.5
depth (ins)	28.5
height (ins)	25.6
weight (lbs)	152

