


# NDX 1350

## 460/3/60 - 1350 scfm refrigerated air dryer

nano R4 refrigerated air dryers are designed for reliability, performance and low cost of ownership. They feature a low pressure drop stainless steel heat exchanger, stainless steel moisture separator, environmentally friendly refrigerants, TXV for precise control and a simple yet powerful electronic controller. The R4 offers piece of mind that downstream equipment will be protected from damaging moisture contamination.



### general characteristics

rated capacity (scfm)*	1350
absorbed power (kW)	6.54
full load amps (A)	14.90
power supply (V/Ph/Hz)	460/3/60

### operating limits

design operating pressure range (psig)	0 - 189
maximum refrigerant working pressure (psig)	392
minimum/maximum ambient temperature (°F)	34 - 110
maximum inlet temperature (°F)	158

### refrigerant gas/circuit

refrigerant type	R407c
refrigerant charge per circuit (lbs)	8.82

### compressors

compressor type	scroll
compressor quantity	1
independent gas circuit	1

### fans

fan type	axial
fan quantity	1

### air circuit

air circuit connections (NPT)	3"
-------------------------------	----

### ISO class

ISO air quality class (water content)	class 4
---------------------------------------	---------

*\*rated flow capacity: conditions for rating dryers are in accordance with ISO7183 (Option A2). Compressed air at dryer inlet: 100 psig (7 bar) and 100°F (38°C); ambient air temperature: 100°F (38°C); operating on 60Hz power supply. For all other conditions, contact support@n-psi.com*

### features

- stainless steel heat exchanger for maximum durability and corrosion resistance
- CAREL advanced electronic controller
- oversized condenser for high ambient temperatures
- robust refrigeration circuit with fan pressure, high refrigerant pressure and low suction pressure switches
- environmentally friendly R134a and R407C refrigerant
- timed solenoid drain for reliable condensate removal
- refrigerant gauge for simple diagnostics
- powder coated aluminum panels
- TXV ensures stable dew point performance under varying loads
- stainless steel inlet and outlet connections
- c-UL listed components
- built in reliability with a 2 year warranty with pre-filtration and non-corrosive piping installed

### advanced microprocessor features

- 3 button digital interface
- dew point display for visual monitoring
- user programmable operating parameters
- status indication for drain, fan and compressor
- drain test and adjustment



## technical specification

### dimensions & weight

length (ins)	23.1
depth (ins)	47.4
height (ins)	39.6
weight (lbs)	882

