

## ND4X 60

### 115/1/60 - 60 scfm refrigerated air dryer

nano R5 NEMA 4 stainless steel refrigerated air dryers are designed for reliability, performance and low cost of ownership. They feature a low pressure drop stainless steel heat exchanger, stainless steel moisture separator, environmentally friendly refrigerants and TXV for precise control. The R5 offers piece of mind that downstream equipment will be protected from damaging moisture contamination.



#### general characteristics

|                        |          |
|------------------------|----------|
| rated capacity (scfm)* | 60       |
| absorbed power (kW)    | 0.25     |
| full load amps (A)     | 12       |
| power supply (V/Ph/Hz) | 115/1/60 |

#### operating limits

|  |          |
|--|----------|
| design operating pressure range (psig)   | 0 - 250  |
| minimum/maximum ambient temperature (°F) | 34 - 110 |
| maximum inlet temperature (°F)           | 180      |

#### refrigerant gas/circuit

|                  |       |
|------------------|-------|
| refrigerant type | R134a |
|------------------|-------|

#### compressors

|                         |        |
|-------------------------|--------|
| compressor type         | piston |
| compressor quantity     | 1      |
| independent gas circuit | 1      |

#### fans

|              |       |
|--------------|-------|
| fan type     | axial |
| fan quantity | 1     |

#### air circuit

|                               |    |
|-------------------------------|----|
| air circuit connections (NPT) | ½" |
|-------------------------------|----|

#### ISO class

|                                       |         |
|---------------------------------------|---------|
| ISO air quality class (water content) | class 4 |
|---------------------------------------|---------|

*in compliance with ADF 100 specifications for compressed air dryers: Inlet temperature: 100°F, ambient temperature: 100°F, inlet pressure: 100 psig, pressure dew point: 33°F to 39°F. For all other conditions refer to the correction factors above or contact support@n-psi.com*

#### features

- stainless steel heat exchanger for maximum durability and corrosion resistance
- NEMA 4 on/off switch
- oversized condenser for high ambient temperatures
- robust refrigeration circuit with fan pressure, high refrigerant pressure and low suction pressure switches
- environmentally friendly R134a refrigerant
- supplied with 6' power cord for plug and play operation
- timed solenoid drain for reliable condensate removal
- refrigerant gauge for simple diagnostics
- stainless steel panels
- TXV ensures stable dew point performance under varying loads
- stainless steel inlet and outlet connections
- c-UL listed components
- built in reliability with a 1 year warranty with pre-filtration and non-corrosive piping installed

**nano-purification solutions llc**  
charlotte, north carolina  
united states

**nano-purification solutions**  
st. catharines, ontario  
canada

**nano-purification solutions ltd**  
gateshead, tyne and wear  
united kingdom

**nano-purification solutions GmbH**  
krefeld, germany


tel: 704.897.2182  
fax: 704.897.2183  
email: support@n-psi.com  
web: www.n-psi.com



## technical specification

### dimensions & weight

|              |     |
|--------------|-----|
| length (ins) | 16  |
| depth (ins)  | 22  |
| height (ins) | 22  |
| weight (lbs) | 160 |



experience