



nano D<sup>1</sup>: Modular Low Dew Point Desiccant Air Dryers

# NDL 040 GFN2 LDP

10 scfm Desiccant Air Dryer

The nano D<sup>1</sup> modular low dew point air dryer provides clean dry air for a wide range of industrial applications. These dryers use the pressure swing adsorption principle in a modular design to dehydrate and purify your compressed air in simple, efficient and compact package. With digital PLC controls that merge energy consumption and provide dew point monitoring, the D<sup>1</sup> modular low dew point desiccant air dryer provides substantial energy savings under various seasonal conditions for critical applications.



GENERAL CHARACTERISTICS	
Rated flow (scfm) <sup>(1)</sup>	10
Regeneration air (scfm)	3
Absorbed power (kW)	0.0264
Power supply (V/Ph/Hz) <sup>(2)</sup>	100-240 VAC/50 or 60 Hz
OPERATING LIMITS	
Design operating pressure range (psig)	58 to 232
Design operating temperature range (°F)	35 to 100
Minimum/maximum ambient temperature (°F)	35 to 122
Maximum inlet temperature (°F)	not to exceed 85
DESICCANT CHAMBERS	
Desiccant type	13X molecular sieve
Desiccant cartridges with integrated afterfilter (kit no)	NDK 040 LDP
CONTROLS / DESIGN	
Dryer design	PSA
Controller type	PLC
NEMA rating	NEMA 1
AIR CIRCUIT	
Air circuit connections (PTC) <sup>(3)</sup>	3/8"
ISO CLASS	
ISO air quality class (water content)	class 1 (-94°F pdp)




(1) In compliance with CAGI (ADF 100) / NFPA (class H): inlet temperature 100°F, ambient temperature 100°F, inlet pressure 100 psig, pressure dew point -94°F. For all other conditions, contact support@airandgassolutions.com.

(2) Optional 24 VDC

(3) NDL 010 to NDL 050 have push to connect fittings on the inlet and outlet. All other models have NPT(F) threaded connections.

## Dimensions & Weight

DIMENSIONS AND WEIGHT	
A (ins)	35.0
B (ins)	10.4
C (ins)	13.0
Weight (lbs)	40.8



# D1: Modular Low Dew Point Desiccant Air Dryers

## Features

- C-ETL-US certification
- Includes a separate GFN M1 and M01 grade prefilters with timer drains (shipped loose) and a built in 1 micron afterfilter.
- Patented combined filter & desiccant cartridge; no afterfilter required
- Advanced PLC controlled operation
- Built in reliability with a 2-year warranty
- Energy saving dew point control (optional)
- Floor or wall mounted installation
- Reliable high-performance valves
- Tower equalization for constant flow and pressure
- Designed for tough industrial settings.
- Integrated compressor synchronization function
- Advanced PLC features: digital interface, digital LED display, outlet air dew point indication (with ES option)
- User programmable operating parameters
- Alarm indication

Technical specifications subject to change without notice.  
Publication Reference: D1-NDL040GFN2LDP-US-EN-Version-000  
©2026 Air & Gas Solutions LLC



# nano

Experience. Customer. Service.

nano-purification solutions  
[www.nano-purification.com](http://www.nano-purification.com)

United States  
Charlotte, North Carolina  
Phone: +1 704 897 2182  
Email: [support@airandgassolutions.com](mailto:support@airandgassolutions.com)

United States | Canada | United Kingdom | Singapore