

COMPULSORY INSTALLATION AT CUSTOMER CARE.
 Disconnect switch + fuses
 Model FLA Largest motor CC fuses RK fuses
 1260W 40 FLA - 32

Select the transformer primary terminal according to the customer power supply

COMPRESSOR MOTOR

- A SB B REMOTE START/STOP
- 15 CR2 16 ALARM SINGAL
- 17 K21 18 RUNNING SINGAL


- 11 12 01.6 1 2 01.1
- 13 14 01.4 3 4 01.1
- 5 6 01.1
- 11 12 01.6
- 21 22 01.6

Note	Position	Modified from	Date	Intr./Appd.
04	04	Update design and add page2	2023-03-18	COX/NU

Parent 3D Model	Ed.Version 3D
-----------------	---------------

Tolerances, if not indicated, according to:			
Name	SERVICE DIAGRAM	DXR1260W-A	Confidentiality class acc. to 1102 K
Material	NOT APPLICABLE		Internal
Treatment	NOT APPLICABLE		ACDE
Scale	1:1	Family	Compare
Drawn by		Blank nr.	Replaces
Drawing format	Blank wt.	Kg	Finl wt.
STATUS	Approved	Prod checked.	Approved.
Approved Internal		Date	9/22/2020 4:09:05 PM
Designation		Sheet	() 01 02
2205686851			

All materials supplied are in compliance with the requirements of the List of Prohibited Substances



COX