



<u>DRAIN PORT TYPE:</u>	<u>MAX. ALLOWABLE WORKING PRESSURE:</u>
AUTOMATIC	16 barg (232 psig)
MANUAL	20.7 barg (300 psig)

GENERAL PROPERTIES	
<u>FILTER MODEL OPTIONS:</u>	
SIZE 1 - GF0006	SIZE 2 - GF0015
<u>PORT SIZE (A) VALID FOR G & NPT CONNECTIONS:</u>	
1/8"	1/4"
<u>FLOW RATE:</u>	
2.8 l/s (6 SCFM)	6.9 l/s (15 SCFM)

FILTER GRADE	FLOW DIRECTION	PARTICLE REMOVAL	MAX OIL CARRYOVER AT 20°C	MAX PARTICLE SIZE CLASS*	MAX OIL CONTENT CLASS*	PRESSURE LOSS - CLEAN & DRY	PRESSURE LOSS - SATURATED	MAX AIR INLET TEMP. WITH AUTOMATIC DRAIN	MAX AIR INLET TEMP. WITH MANUAL DRAIN	END CAP COLOUR
M1	N	-	0.3mg/m ³	3	3	55mbar (0.8psi)	125mbar (1.8psi)	80°C (176°F)	N/A	RED
M01	N	-	0.01mg/m ³	1	2	85mbar (1.2psi)	125mbar (1.8psi)	80°C (176°F)	N/A	BLU
AC	N	-	0.003mg/m ³	-	1	115mbar (1.7psi)	-	N/A	50°C (122°F)	BLK
RM1	REV	1µm	-	3	-	55mbar (0.8psi)	-	N/A	120°C (248°F)	RED

* CLASS IN ACCORDANCE WITH ISO8573-1:2010
 ** FLOW DIRECTION VISUALLY INDICATED ON FILTER HOUSING

		PROJECT REFERENCE				DRG. TITLE	DRG. NUMBER	MATERIAL	CHECK
		DESIGN REF				SIZE 1 & 2 FILTER SPECIFICATION	A3- 42-1419	N/A	IA
CREATED BY	DATE	REVISED BY	DATE	BY	DATE				
IA	29.7.19	JL	9.9.19	JL	9.9.19				
B DETAILS MODIFIED		9.9.19		JL	9.9.19				
REV	CHANGE ORDER	DATE	DATE	BY	DATE				