NSS 4200 MRK

Maintenance Kit Installation Guide



Before starting assembly, please check contents are as follows:

- 4 filters (remove from plastic bag)
- 2 white prefilter bag
- 4 metal retaining springs (460 mm)

Service interval kit containing:

- printed card
- self-adhesive time strip

Service indicator - assembly and attachment



- Insert the boss on the reverse of the mount (c) into the predrilled hole in the separator lid.
- Peel backing from time strip (a) and attach to the plastic card (b) within the dotted lines.
- Flex the card, passing the ends through the slots on the top surface of the mount.

To activate, press firmly on the time strip label at the point indicated.

After a few minutes, a red line will appear, to indicate 'time in service' up to 12 months.

A replacement card and time strip will be supplied with each service kit.

General installation notes

- Please ensure a steady fall in the pipe run from the outlet point to the sanitary drain.
- When used in conjunction with timed solenoid drain, set drain "open" duration to minimum setting (1-2 seconds).
- When used in conjunction with motorized ball valve or high capacity drain (ie Drain-all®) a de-pressurisation chamber must be installed between drain and NSS unit.
- Never discharge condensate to a storm drain or to surface water; always connect to a sanitary drain or sewer.
- Remember that it's the user's responsibility to check with the local authority as to the permissible discharges in their area.

Testing quality

Replace filters before outlet cloudiness exceeds the ppm limit for your region.

Test outlet quality weekly using kit



NSS 4200 MRK

Installation guide















Address: 5509 David Cox Road

Charlotte NC 28269, USA 704.897.2182 Fax: 704.897.2183

E-mail:

Internet: www.nano-purification.com support@nano-purification.com E-mail:

Address: Dukesway

Team Valley Trading Estate, Gateshead NE11 OPZ, United Kingdom

+44 (0) 191 497 7700 Internet: www.nano-purification.com sales_uk@nano-purifcation.com